



AKRON DISPERSIONS

3291 Sawmill Road
P.O. Box 4195
Akron, Ohio 44321

Phone: 330-666-0045
Fax: 330-666-7842

Product Data Sheet

Product:

BOSTEX 759

Description:

A 50% active aqueous emulsion of p-Oriented Styrenated Diphenylamine and Di(Tridecyl)Thiodipropionate.

Specifications:

Appearance / Color :	Off-White
Active Solids :	50%
Total Solids :	52.6% - 54.6%
pH :	8.0 – 10.0
Viscosity(Tentative) :	1000 – 2000 cps(RVF #3 @ 10 RPMs)
Mean Particle Size :	Less than 5 Microns
Storage :	Protect from freezing. Stir before using.
Recommended Shelf Life :	6 Months



AKRON DISPERSIONS, INC.

MATERIAL SAFETY DATA SHEET

Page 1 of 3

SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: **Bostex 759**

CHEMICAL NAME: Aqueous Mixture of p-Oriented Styrenated Diphenylamine(CAS# 68442-68-2),
Di(Tridecyl)Thiodipropionate(CAS# 10595-72-9), Sodium Dodecylbenzene Sulfonate
(CAS# 25155-30-0/68081-81-2)

MANUFACTURER: Akron Dispersions, Inc.
3291 Sawmill Road P.O. Box 4195
Akron, Ohio 44321

TELEPHONE NUMBER: (330)666-0045

EMERGENCY TELEPHONE NUMBER: (330)666-0045

FAX: (330)666-7842

SECTION 2 HAZARDOUS INGREDIENT INFORMATION

None Known

SECTION 3 HAZARDS IDENTIFICATION

Health Hazards(Acute and Chronic): Prolonged skin contact may cause irritation.

HMIS: Health-1 Flammability-0 Reactivity-0 Personal Protection-B

SECTION 4 FIRST AID MEASURES

Eye Contact: Flush with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact: Wash affected area with soap and water. Consult a physician if irritation persists.

Inhalation: Remove to fresh air. If breathing is difficult, seek medical attention.

Ingestion: Seek immediate medical attention.

SECTION 5 FIRE & EXPLOSION HAZARD

Flashpoint: N/D Flammable Limits: N/D

General Hazard: Wear MSHA-NIOSH approved Self-Contained Breathing Apparatus

Extinguishing Media: CO₂, Dry Chemical, Waterspray, Foam

Decomposition Products Under Fire Conditions: Oxides of Carbon, Nitrogen, Sodium, and Sulfur, Hydrogen Sulfide

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Absorb with inert material. Sweep, vacuum, or shovel into appropriate container.

SECTION 7 HANDLING AND STORAGE

Storage: Store in a cool, dry area.
Storage Temperature: Above 32°F

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

OSHA Regulation 29CFR1910.1000 requires the following PEL Limits: N/D
The ACGIH recommends the following Occupational Exposure Limit: N/D
Personal Protection: Gloves, Goggles, and Apron recommended
Ventilation: Local Exhaust

SECTION 9 TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Product Appearance: White to Off-White Liquid

Boiling Point(°F): 212	Freezing Point(°F): 32
Vapor Pressure(@150°C): N/A	Specific Gravity(Approx.): N/D
Vapor Density: N/A	% Volatile by Volume: 50%
Solubility in Water: Miscible	Evaporation Rate: N/A
pH: 8-11	

SECTION 10 STABILITY AND REACTIVITY DATA

Stability: Stable
Conditions To Avoid Instability: None Known
Materials And Conditions To Avoid Incompatibility: Acids, Alkali, Oxidizing Materials, Rubber, Steel
Hazardous Decomposition Products: Oxides of Carbon, Nitrogen, Sodium, and Sulfur, Hydrogen Sulfide
Hazardous Polymerization: Will Not Occur
Conditions To Avoid Hazardous Polymerization: None Known

SECTION 11 TOXICOLOGICAL INFORMATION

Carcinogenicity(NTP/IARC/OSHA): None.

SECTION 12 ECOLOGICAL INFORMATION

Not determined

SECTION 13 DISPOSAL

Waste Disposal Method: Dispose per Local, State, and Federal Regulations

SECTION 14 TRANSPORT INFORMATION

DOT: Not a DOT controlled material(United States).

SECTION 15 REGULATORY INFORMATION

TSCA: All ingredients of this product appear on the TSCA Inventory

SARA Title III-Section 313: This product does not contain a toxic chemical in excess of 1% of the mixture(0.1% if a listed carcinogen).

SECTION 16 OTHER INFORMATION

Prepared By: D. Hunsicker

Date: January 13, 2010

The information in this MSDS was compiled from sources which we believe are accurate and reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt such safety precautions as may be necessary. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with the handling, storage, use, or disposal of this product.